# SL-PU UV HD

## Declaration of performance according to Regulation (EU) No 305/2011, Annex III (Construction Products Regulation)

| | |
|---|---|
| **1.** Unique identification code of the product-type: | Screeds and screed materials |
| **2.** Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4): | SL-PU UV HD, batch no.: see packaging |
| **3.** Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: | Two-component aliphatic polyurethane self-levelling floor. EN 13813: SR – B1,5 – AR1 – IR4 |
| **4.** Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): | Quartzline B.V., W.A. Boogaerdtstraat 5, NL-3316 BN Dordrecht |
| **5.** Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): | Not relevant (see point 4) |
| **6.** System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V of the Construction Products Regulation: | System 3 for reaction to fire, System 4 for the other characteristics |
| **7.** Notified body (harmonised standard): in case the declaration of performance concerns a construction product covered by a harmonised standard: | WFRGENT N.V., Ottergemsesteenweg-Zuid 711, 9000 Ghent, Belgium (notified body No. 1173) performed the fire tests under System 3 and issued classification report No. 13659C. |
| **8.** Notified body (ETA): in case the declaration of performance concerns a construction product for which a European Technical Assessment has been issued: | Not relevant |

## 9. DECLARED PERFORMANCE

| Essential characteristics | Performance | Standard | Harmonised technical specification |
|---|---|---|---|
| **Reaction to fire** | Bfl-s1 | EN 13501-1 | EN 13813 |
| **Release of corrosive substances** | SR | EN 13813 | EN 13813 |
| **Water vapour permeability** | NPD | EN ISO 7783-1 | EN 13813 |
| **Abrasion resistance** | ≤ AR1 [1)] | EN 13892-4 | EN 13813 |
| **Bond strength** | ≥ B1,5 | EN 13892-8 | EN 13813 |
| **Impact resistance** | ≥ IR4 | EN ISO 6272 | EN 13813 |
| **Sound insulation** | NPD [2)] | EN ISO 140-1 | EN 13813 |
| **Sound absorption** | NPD | EN ISO 354 | EN 13813 |
| **Thermal resistance** | NPD | EN 12664 | EN 13813 |
| **Chemical resistance** | NPD | EN 13529 | EN 13813 |

1) Minimum classification.
2) No Performance Determined

CE

**Quartzline BV**
**18**
DoP11PUHD018
**EN 13813:2002**

## 10. DECLARATION

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:
Dordrecht, 5 November 2018



**Peter Groeneweg**
Research and Development