

QUARTZLINE CEM LAVA

Version 1.0 - March 2025

CEM LAVA consists of fine mineral grains combined with two-component epoxy resin binder. The result is an extremely durable and exceptionally scratch resistant floor



CEM LAVA

Product	Usage GR/M²	Packing	Discription	Tool
LAYER 1				
Primer Universal	130 gr Primer + 390 gr water	10kg	Universal primer	Nylon roller
LAYER 2				
Alpha SL 2-20	1650 per mm	25 kg	For calcium sulfate-based substrates such as anhydrite and alpha hemihydrate.	Notched leveling rake
OR				
Cementitious SL 2-20	1650 per mm	25 kg	For concrete and cement-based substrates.	Notched leveling rake
LAYER 3				
Primer CL	150-200	7,5 kg	The grains in the primer ensure good adhesion of the Cem Lava Base.	Nylon roller
LAYER 4				
Cem Lava Base	800-1000	20 kg	This is the coarse layer	Spackle knife
LAYER 5				
Cem Lava Top	600-800	10 kg	This is de fine layer	Spackle knife
LAYER 6				
Coating PU MG Matt	125-150	5 kg	This coating has good abrasion resistance and provides a matte finish	Microfiber roller



Coating PU MG Matt

CEM LAVA Top

CEM LAVA Base

Primer CL

Alpha SL 2-20
Cementitious SL