


QUARTZLINE PUCEM TF

Version 1.0 – October 2026

PUCEM TF is a slip-resistant, broadcast polyurethane cement system for a layer thickness of 4 to 12 mm, widely used in industry. The broadcast quartz ensures safe walking on a wet floor. The seamless finish is hygienic and meets strict food safety standards.



PUCEM TF: PRODUCT OPTIONS PER LAYER

Product	Description	Consumption
LAYER 1: Self-levelling layer		
PUCEM TF	Polyurethane cement broadcast system	4 mm: approx. 7.4 kg/m ² 8 mm: approx. 14.8 kg/m ² 12 mm: approx. 22.2 kg/m ²
LAYER 2: Broadcast layer		
 Broadcast sand 0.4-0.8 mm	Coloured quartz for slip resistance	approx. 4 kg/m ²
 Mortar 0.8-1.4 mm	Coarser quartz for higher slip resistance	approx. 4 kg/m ²
LAYER 3: Topcoat		
PUCEM L	Polyurethane cement sealer	0.8–1.2 kg/m ²

PROPERTIES

-  Wear-resistant and suitable for heavy loads
-  Resistant to chemicals, oils and solvents
-  Heat-resistant, including hot water
-  Hygienic and liquid-tight
-  Slip-resistant

LAYER THICKNESS

4–12 mm

COLOURS

PUCEM colours

APPLICATIONS

- Food industry
- Chemical industry
- Pharmaceutical industry
- Dairy industry
- Commercial kitchens
- Bottling lines