


QUARTZLINE CEM DECORATIVE

Version 1.0 – October 2026

CEM Decorative is a cement-based self-levelling floor for a modern floor with a concrete-like appearance. Its white base, combined with the Quartzline colour mixing system, makes almost any colour possible. The final concrete look is shaped by the hand of the applicator.



CEM DECORATIVE: PRODUCT OPTIONS PER LAYER

Product	Description	Consumption
LAYER 1: Primer or scratch coat		
 Primer BHH	Epoxy primer for porous substrates	150–300 g/m ²
 SL-EP Scratchcoat	Epoxy scratch coat for pore filling and levelling	500–1,500 g/m ²
LAYER 2: Broadcast layer		
 Mortar 0.4-0.8 mm	Quartz broadcast for adhesion	approx. 2 kg/m ²
LAYER 3: 2nd primer		
 Primer Universal	Acrylate primer for porous substrates	150–500 g/m ²
LAYER 4: Self-levelling layer		
 Cementitious SL Decorative	Coloured cement-based self-levelling floor, 3–10 mm	1.6 kg/m ² per mm
LAYER 5: 1st topcoat		
 Coating CSL	Acrylate coating for topcoat adhesion	150 g/m ²
LAYER 6: 2nd topcoat		
 Coating PU MG Matt	Topcoat for a matt finish	125–150 g/m ²
 Coating PU MG Satin Gloss	Topcoat for a satin finish	125–150 g/m ²

PROPERTIES

-  Concrete-look finish
-  Almost any colour
-  Good mechanical properties
-  Fast curing
-  Seamless

COLOURS

RAL
NCS
Sikkens
Cementitious special colours
Micro QL

APPLICATIONS

Residences
Hospitality
Retail
Healthcare

