

QUARTZLINE STONE OUTDOOR

Version 1.0 – October 2026

STONE Outdoor is a polyurethane-bound gravel floor for outdoor use. The polyurethane binder allows the floor to expand and contract and makes it resistant to UV radiation. Available in grain sizes 1-2, 2-3 and 3-4 mm, in all colours and also metallic.



STONE OUTDOOR: PRODUCT OPTIONS PER LAYER

Product	Description	Consumption
LAYER 1: Primer		
 Primer BHH	Epoxy primer for porous substrates	150–300 g/m ²
 Primer GW	Epoxy primer for closed substrates	100–150 g/m ²
LAYER 2: Aggregate layer with binder		
 Siergrind 1-2 mm	UV-resistant coloured quartz	approx. 11 kg/m ²
 Siergrind 2-3 mm	UV-resistant coloured quartz	approx. 13 kg/m ²
 Siergrind 3-4 mm	UV-resistant coloured quartz	approx. 14 kg/m ²
 Binder UV	Two-component PU binder	3.5 kg per 50 kg aggregate
 Binder UV 1K	One-component PU binder	660–840 g/m ²

PROPERTIES

-  Suitable for outdoor use
-  UV-resistant
-  Flexible, can expand and contract
-  Many colours and patterns
-  Seamless

COLOURS

Quartz
Quartz Metallic

APPLICATIONS

Balconies
Patios
Walkways
Outdoor stairs
Around swimming pools
Driveways
Terraces

